

LW6010 SPECIFICATIONS

halo floor mounted toilet

FEATURES:

- Streamlined, floor mounted, in wall tank
- Vitreous china
- Dual flush consumption (0.8 gpf / 3 lpf or 1.6 gpf / 6 lpf)
- Elongated bowl with large water surface
- Powerful, quiet flush every time
- Includes anchor bolts to fasten to floor
- Skirted styling for easy cleaning
- Requires waste outlet

SPECIFICATIONS:

Water Use:	0.8 gpf (3 lpf) or 1.6 gpf (6 lpf)
Flush System:	Recommend Geberit in-wall carrier 109.304.00.5
	Rear discharge into wall:
	Requires Geberit waste fittings 366.887.16.1 and 366.061.16.1
	Rear discharge into floor:
	Requires Geberit waste fitting 152.647.00.1
	(Geberit items not included)
Min. Water Pressure:	20 psi
Water Surface:	5¼" x 4¼" (133mm x 108mm)
Warranty:	One Year Limited Warranty
Material:	Vitreous China
Shipping Weight:	80lbs (36.5kg)*
Shipping Dimensions:	(LWH) 26" x 21" x 19" (655mm x 530mm x 480mm)

FINISHES:

White

ACCESSORIES:

- Geberit flush actuator (not included)
- LSeat-004 - Soft closing, quick release duroplast seat & lid (not included)
- LSeat-slim, ultra slim duroplast soft-close, quick-release toilet seat (not included)
- LB9010 coordinating bidet (sold separately)

INSTALLATION NOTES:

Install this product according to the installation guide. Our products must be installed by certified professionals only. Refer to manufacturer and local codes for flush valve requirements.

CODES / STANDARDS APPLICABLE:

- Meets or exceeds ANSI / ASME standard A112.19.2 and CAN / CSA B 45 requirements
- ASME A112.19.2.2003
- IAPMO / UPC / cUPC
- ASME A112.19.5-2005 / CSA B125.3-2005
- CSA B45.0; CSA B45.1
- Calgreen & WaterSense compliant



*Approximate measurements for comparison only.

Note: These dimensions and specifications are subject to change without notice.

