TECHNICAL DATA SHEET

Product Family

EC30 Series Contactors
DiversiTech Definite Purpose Contactors

Description

Definite purpose contactors can be used for heating, air conditioning, refrigeration, data processing, and food service equipment. Quick connect terminals provide for easy wiring. This contactor comes as a two pole on a small frame.

Features

- Cost effective
- Easy to install
- UL Recognized



HVAC Contactor

Specifications

Coil Voltage:

120 VAC

24 VAC

240 VAC

Certifications:

UL Recognized

Mounting:

Foot Mounting

Warranty:

1 year



EC30224



EC40224



DIVERSITECH

EC302240



EC402120



EC402240



STOCK NO	Coil VA	FL Amps	Pole	Dimensions (in)	Weight (lbs)	Mounting
EC30224	24	30	2	H = 2.75 , W = 2.5, D = 3.75	0.8	Foot
EC302120	120	30	2	H = 2.63 , W = 2.25, D = 3.75	0.68	Foot
EC302240	240	30	2	H = 2.25, W = 2.75, D = 3.63	0.8	Foot
EC40224	24	40	2	H = 2.75 , W = 2.25, D = 3.75	0.6	Foot
EC402120	120	40	2	H = 2.75 , W = 2.5, D = 3.25	0.6	Foot
EC402240	240	40	2	H = 2.5 , W = 2.75, D = 3.5	0.6	Foot