

PROLINE® XE HIGH EFFICIENCY NON-CONDENSING POWER DIRECT VENT

PROLINE® XE
— BEST —



ENERGY STAR® Qualified

- All models (except GPDx 75L) meet the ENERGY STAR® requirement and may also qualify for local utility and rebate programs.

Power Direct Vent Design

- Combined horizontal and vertical vent runs up to 180 equivalent feet with 4" diameter venting (ABS, PVC, CPVC and polypropylene).
- Two-pipe sealed combustion system uses outside air, eliminating problems caused by insufficient indoor ventilation.
- Reduced NOx emissions comply with air quality management district regulations.

Quiet and Efficient Blower

- Factory-installed 6-foot power cord with standard 3-prong male connector provided.
- Electrical requirements; 110/120 VAC power source, less than 5 amp draw.

Hot-surface Ignitor

- More robust and reliable than standing pilot, and reduces energy consumption.

Dynaclean™ Diffuser Dip Tube

User-Friendly

- State-of-the-art electronic gas control provides more precise temperature control.
- LED control light displays operation status and diagnostics information.
- Built-in heat traps
- Water inlet and outlet reduce the amount of heat lost through piping.

Enhanced-Flow Brass Drain Valve

Design-Certified by CSA Group

- Certified at 300 psi test pressure and 150 psi working pressure.
- Listed according to ANSI Z21.10.1-CSA 4.1 standards or ANSI Z21.10.3 CSA 4.3 standards governing storage tank-type water heaters governing storage tank-type water heaters.

Available in Natural Gas and Propane

6-Year Limited Tank and Parts Warranty

- For complete information, consult written warranty or go to hotwater.com.



Model Number	Series	Nominal Capacity	Rated Storage Volume	First Hour Rating (Gallons)	UEF	NG Input Per Hour Propane	Recovery @ 90°F Rise Gallon Per Hour	Dimensions in Inches			Approx. Shipping Weight (lb)
								Height to Top of Blower	Height to Top of Tank	Diameter	
GPD _L 40	200	40	38	74	0.68	40,000	45	58-1/4	49-5/8	22	174
GPD _T 50	200	50	48	81	0.72	45,000	50	67-1/2	58-3/4	22	192
GPD _X 50L	200	50	48	118	0.73	62,000*	73	69	60-1/4	22	200
† GPD _X 75L	210	75	72	129	0.68	76,000	82	70-5/8	61-1/2	26	277

*Propane model has input of 58,000 BTU/hr.

Natural gas models cited are series 200/210. Propane models are series 201/211.

Side connections are standard on GPD_X models.

For side connect models, add "L" to the model number (example: GDPT-50L).

Side connections available on GPD_L and GPD_T models.

All models are certified from sea level to 10,100 ft. elevation.

† GPD_X-75 is not ENERGY STAR® Qualified.