

PROLINE® XE HIGH EFFICIENCY NON-CONDENSING FLUE DAMPER



ENERGY STAR® Qualified

- All models meet the ENERGY STAR® requirement and may also qualify for local utility and rebate programs.

Green Choice® Gas Burner

- Patented eco-friendly burner design reduces NOx emissions up to 33% and complies with Low-NOx emission requirements of 40 ng/J.

DynaClean™ Diffuser Dip Tube

CoreGard™ Anode Rod

Requires 120V Power

- Power cord with standard 3-prong male connector provided.
- Electrical requirements; 110/120 VAC power source, less than 5 amp draw.

Blue Diamond® Glass Coating

Enhanced-Flow Brass Drain Valve

Code Compliance

- Meets IBC, CEC, and HUD (excluding mobile homes) National Codes.
- Meets the efficiency requirements of the U.S. Department of Energy and current edition of ASHRAE/IES 90.1.

Design-Certified by CSA Group

- Certified at 300 psi test pressure and 150 psi working pressure.
- Listed according to ANSI Z21.10.1 – CSA 4.1 standards governing storage tank-type water heaters.

6-Year Limited Tank and Parts Warranty

- For complete information, consult written warranty or go to hotwater.com.



Model Number	Nominal Capacity	Rated Storage Volume	First Hour Rating (Gallons)	UEF	BTU Input Gallon Per Hour Natural*	Recovery @ 90°F Rise Gallon Per Hour	Dimensions in Inches				Approx. Shipping Weight (lbs)
							Height to Top of Draft Hood	Height to Top of Tank	Diameter	Draft Hood Outlet	
Tall Models											
GCF-40	40	38	70	0.64	40,000	42	64-1/4	58-1/4	20	3" or 4"	152
GCF-50	50	48	84	0.69	40,000	42	63-1/2	57-1/4	22	3" or 4"	167
Short Models											
GCFL-40	40	38	65	0.66	40,000	42	54	47-3/4	22	3" or 4"	149
*GCFL-50	50	49	78	0.69	40,000	42	55-3/4	49-1/2	24	3" or 4"	175

Water connection is 3/4" on all models

All models are certified from sea level to 10,100 ft. elevation

PROLINE® XE
BEST