

HYDRONIC HEATING PRODUCTS

Hydronic Heating Specialties

MODEL FF

ALL BRONZE FEED WATER PRESSURE REGULATORS



Available in 1/2" union threaded, threaded and solder union configurations. Purge lever/fast fill feature. Cartridge replaceable in-line.

FEATURES

- No cage screws to rust
- Individually set at 15 psig - Adjustable 10 to 25 psig
- Temperatures to 210°F
- Heavy pattern bronze body and spring cover
- High capacity
- SS strainer, in-line, standard
- Choice of inlet connections

Model Number	Part Number	Size (in.)	Height (in.)	Length (in.)	Wt./100 (lbs.)
FF12	35-503-01	1/2 Union Threaded	5.25	4.31	255
FFT12	35-603-01	1/2 Threaded	5.25	3.50	225
FFS12	35-703-01	1/2 Solder Union	5.25	3.18	232

MODEL FFB

ALL BRONZE COMBINATION DCAP BACKFLOW PREVENTER AND FEED WATER REGULATORS



Positive protection against backflow when supply pressure falls below system pressure. Assembly combines FWR feedwater regulator and DCAP dual check assembly backflow preventer.

FEATURES

- Purge lever/fast fill feature
- Designed for continuous pressure, hot or cold water service
- Built-in strainer
- Max pressure 175 psig
- Max temp 210°F
- Series 40-400 Backflow device is ASSE and CSA listed



Model Number	Part Number	Size (in.)	Height (in.)	Length (in.)	Wt./100 (lbs.)
FFB12	35-6A3-BF	1/2 Union NPT x NPT	5.25	8.50	450
FFBS12	35-6H3-BF	1/2 Solder Union x NPT	5.25	8.50	440
FFB12C	35-6A3-BFC*	1/2 Union NPT x NPT	5.25	8.50	450
FFBS12C	35-6H3-BFC*	1/2 Solder Union x NPT	5.25	8.50	440

*"C" Models for Canadian market - Discharge port not threaded.