

Description	Value
General information:	
Product name:	UNILIFT AP12.40.04.1
Product No:	96023926
EAN number:	5700390548827
Technical:	
Maximum flow:	61.6 US GPM
Maximum head:	32.81 ft
Type of impeller:	SEMI OPEN
Max. Particle:	0.47 in
Approvals:	CCSAUS,PROP65
Rated speed:	3350 rpm
Materials:	
Pump housing:	Stainless steel
Pump housing:	EN 1.4301
Pump housing:	AISI 304
Impeller:	Stainless steel
Impeller:	EN 1.4301
Impeller:	AISI 304
Cable union:	Brass
Cable union:	CW602N
Cable union:	C35330
Installation:	
Range of ambient temperature:	32 .. 131 °F
Type of connection:	NPT(F)
Size of connection:	1 1/2 inch
Maximum installation depth:	9.84 ft
Inst dry/wet:	D/S
Installation:	horizontal or vertical
Place of installation:	Indoor/outdoor
Liquid:	
Liquid temperature range:	32 .. 131 °F
Density:	62.29 lb/ft³
Electrical data:	
Power input P1:	0.939 HP
Motor type 1-phase:	PSC
Rated power - P2:	0.5 HP
Mains frequency:	60 Hz
Rated voltage:	1 x 115 V
Rated current:	8 A
Starting current:	24 A
Cos phi - power factor:	0.99
Rated speed:	3350 rpm
Capacitor size - run:	20 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Built-in motor protection:	CONTACT
Thermal protec:	internal
Length of power cable:	9.84 ft
Type of cable plug:	US
Others:	
Net weight:	22.5 lb
Gross weight:	24.7 lb
Shipping volume:	1.17 ft³
Country of origin:	HU
Custom tariff no.:	8413.70.2004

