


Flex Vent Lengths

	2" Flex			
	Is manufactured from polypropylene. 2" Flex can be field cut and is ideal for use in chimneys with offsets. With couplers, 2" Flex can be connected to 2" Flex or InnoFlue® SW.			
	Nominal Diameter	Part	Coil Length	Max O.D.
	2" (60)	IFVL02025	25' (7.6m)	2.3 (58)
	2" (60)	IFVL02035	35' (10.7m)	2.3 (58)
	2" (60)	IFVL02050	50' (15.2m)	2.3 (58)
	2" (60)	IFVL02150	150' (45.7m)	2.3 (58)

	3" and 4" Flex			
	Are manufactured from polypropylene and feature rigid sections every 2'. 3" and 4" Flex can be field cut and are ideal for use in chimneys with offsets. The base of your 3" and 4" Flex can be connected to InnoFlue® SW at any rigid section without coupler. Flex-to-Flex couplers available for extended flex runs.			
	Nominal Diameter	Part	Coil Length	Max O.D.
	3" (80)	IFVL03025	25' (7.6m)	3.3 (84)
	3" (80)	IFVL03035	35' (10.7m)	3.3 (84)
	3" (80)	IFVL03040	40' (12.2m)	3.3 (84)
	3" (80)	IFVL03050	50' (15.2m)	3.3 (84)
	3" (80)	IFVL03150	150' (45.7m)	3.3 (84)
	4" (110)	IFVL04025	25' (7.6m)	4.3 (110)
	4" (110)	IFVL04035	35' (10.7m)	4.3 (110)
	4" (110)	IFVL04040	40' (12.2m)	4.3 (110)
	4" (110)	IFVL04050	50' (15.2m)	4.3 (110)
	4" (110)	IFVL04080	80' (24.4m)	4.3 (110)