

# MCG Series

## Cased Multi-Position Coils

### SPECIFICATIONS

Coil Model	Flowrator Size		Dimensions (inches)			Shipping Information	
	R22	R410A	W	D	H	Rows	Weight (lbs)
MCG1824PADP		0.053	14.5	21	20.5	4	53
MCG1824PBDP		0.053	17.5	21	20.5	4	53
MCG1824PA1P		0.053	14.5	21	16.5	3	38
MCG1824PB1P		0.053	17.5	21	16.5	3	38
MCG1824PC1P		0.053	21	21	16.5	3	38
MCG1824TA1P	Factory installed TXV		14.5	21	16.5	3	38
MCG1824TB1P	Factory installed TXV		17.5	21	16.5	3	38
MCG1824TC1P	Factory installed TXV		21	21	16.5	3	38
MCG18PA3P		0.049	14.5	21	16.5	3	46
MCG18PB3P		0.049	17.5	21	16.5	3	46
MCG18PC3P		0.049	21	21	16.5	3	46
MCG2430PA3P		0.059	14.5	21	16.5	3	46
MCG2430PB3P		0.059	17.5	21	16.5	3	46
MCG2430PC3P		0.059	21	21	16.5	3	46
MCG24PA4P		0.053	14.5	21	16.5	3	46
MCG24PB4P		0.053	17.5	21	16.5	3	46
MCG24PC4P		0.053	21	21	16.5	3	46
MCG24TA4P	Factory installed TXV		14.5	21	16.5	3	46
MCG24TB4P	Factory installed TXV		17.5	21	16.5	3	46
MCG24TC4P	Factory installed TXV		21	21	16.5	3	45
MCG3036PAEP		0.067	14.5	21	20.5	4	56
MCG3036PBEP		0.067	17.5	21	20.5	4	56
MCG3036PCEP		0.067	21	21	20.5	4	56
MCG3036PA4P		0.067	14.5	21	16.5	3	46



### STANDARD SPECIFICATIONS

- Rifled copper tubing, enhanced aluminum fins
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed
- Right-hand refrigerant and plumbing connections
- Externally mounted flowrator body with Schrader valve for hiss-testing
- Heavy duty plastic drain pans on most models
- Upflow, horizontal right, or horizontal left without field model modification. Downflow application require plate kit, included.
- Painted cabinets feature furnace connectors
- Fully insulated cabinets with faced insulation
- Split access doors in front for easy service
- AHRI certifiable with all brands of A/C and heat pump systems
- ETL listed for use with both R-22 and R-410a when proper metering device is used

*Supply plenum opening size  
cabinet width -1" x cabinet depth -1".*