



GL SERIES

Single Coil Glass Lined Indirect Water Heaters

- East to Install
- Low Pressure Drop
- Magnesium Anode Rod
Corrosion Protection
- Enameled Coated Steel Tank and Coil
- Minimal Standby Losses
- Tank Jacket Artificial Leather Casing
- Aquastat Sensor Well
- Temperature Pressure Relief Valve
- Residential Limited Warranty:
Tank, 7-Years; Parts, 2-Years
- Commercial Limited Warranty:
Tank, 5-Years; Parts, 2-Years



**As rugged as the outdoors...
for dependable comfort every day**

GL Series | Indirect Water Heaters

Item Number	Model	Storage Volume	Coil Heating Surface	Dimensions (Inches)		Piping Connections N.P.T.		Approx. Wgt.
		Gallons	Square Feet	Height	Diameter	Domestic Water In/Out	Boiler Water In/Out	(lbs.)
H2OIG40GM	GMGL40I	42	14	45	24	1	1	180
H2OIG50GM	GMGL50I	53	14	51	24	1	1	200
H2OIG80GM	GMGL80I	79	20.7	48	30	1	1	243
H2OIG105GM	GMGL105I	106	26	62	30	1	1	393

Item Number	Model	Max. First Hour Rating	Continuous Rating	Boiler Output Needed	Boiler Water Flow Through the Coil	Pressure Drop Through the Coil
		Gal./Hr. @	Gal./Hr. @	MBH	(Gal./Min.)	(Ft. Water)
		115° F	115° F			
H2OIG40GM	GMGL40I	198	162	105	14.0	10.7
		256	220	120		
H2OIG50GM	GMGL50I	212	169	110	14.0	10.7
		310	268	140		
H2OIG80GM	GMGL80I	228	164	110	14.0	15.9
		346	281	180		
H2OIG105GM	GMGL105I	270	175	115	14.0	19.7
		440	345	220		

Note: All ratings are based on 180° F boiler water supply temperature. Domestic hot water 70° F rise, 45° F water inlet temperature. Specifications subject to change without notice."

Standard Equipment

Smooth enameled coil, magnesium anode rod and temperature pressure relief valve, Honeywell Aquastat. Water tank temperature gauge.



Location for Pressure Relief Valve (field installed)

Honeywell Aquastat I4080B135 (field installed)

All ratings and specifications subject to change
PN# 240012396 Rev. 8/18



2201 Dwyer Ave., Utica, NY 13501 • Phone: 315-797-1310 • Fax: 866-432-7329