




VIESSMANN

WALL-MOUNTED GAS CONDENSING BOILER

Space Heating or Combi Boiler
Ideal for Condominiums and Single-Family Homes
VITODENS 100-W



**Delivering peace of mind
for generations to come**

The all new Vitodens
100 offers the perfect
combination of value,
quality and Viessmann
technology.

▲ The new Vitodens: Peace of mind through future-proof design. The perfect combination of value, quality and Viessmann technology. ▲



The Vitodens 100-W offers a reliable, compact solution for heating and on-demand domestic hot water (B1KE)

Equipped with a Viessmann stainless steel heat exchanger for lasting performance and reliability, plus a fully modulating MatriX Plus cylinder gas burner, the Vitodens 100-W wall-mounted condensing boiler is the perfect combination of value, quality and Viessmann technology.

Its compact design, zero clearance to combustibles and extremely quiet operation make the Vitodens 100-W an ideal choice for even the smallest spaces. Plus, with a limited residential lifetime warranty, you can be sure your investment will deliver long-lasting value.

Vitodens 100-W: Outstanding Versatility

The Vitodens 100-W offers the right solution for every demand, including space heating or all-in-one combi options; multiple venting options and boiler software that adjusts automatically for vent length with no added coding; and flexible fuel options, with the ability to switch from natural gas to propane at the push of a button, no conversion kit required.

Installation, service and maintenance are designed to be fast and easy with all pipe connections located at the bottom, and serviceable components easily accessible from the front. The adjustable user interface control panel can be moved easily from bottom to top in order to accommodate different height installations.

Domestic Hot Water To Fit Your Family's Needs

The new Vitodens 100 is available as a B1KE model combi,

offering an outstanding continuous draw rate of up to 4.7 GPM[†] plus added cost savings with the energy-saving on-demand design, or as a B1HE model non-combi boiler.

For more hot water on demand, the B1HE (non-combi) makes an excellent pairing with Vitocell DHW tanks. With an integrated indirect circulator, this combination delivers highly efficient, dependable hot water and space heating for families. A DHW recirculation pump can also be used with a range of scheduling options that match your lifestyle (with regular use, B1HE models).

Save, Learn and Have Peace of Mind From Anywhere

The Vitodens 100-W offers an integrated WiFi interface, which allows the system to connect directly to the internet allowing for seamless integration with the ViCare App for smartphone or tablet. Once ViCare is connected, homeowners can remotely connect to their boiler and utilize on-demand DHW recirculation, DHW scheduling and temperature control, and visualize fuel usage and cost-savings.

With ViCare, homeowners can connect directly to their preferred contractor for scheduled maintenance, preventative service and emergency messages, maximizing reliability and peace of mind that their home's heating is up and running from anywhere.

* On-demand domestic hot water available with Vitodens 100 B1KE models

† B1KE-199 at $\Delta t = 77^{\circ}\text{F}$ (43K). DCW and DHW temperature rise would be proportional. Maximum DHW supply temperature is 140°F (60°C).

**Lambda Pro Plus Combustion Control:
The Heart Of Your Heating**

The proprietary Viessmann modulating Lambda Pro Plus combustion control offers clean combustion, 10:1 turn down ratio and quiet operation with either propane or natural gas, which can be changed at the push of a button.



Low-emission, Viessmann-made MatriX Plus cylinder burner

**Stainless Steel Inox-Radial Heat Exchanger:
Efficient And Reliable**

The Vitodens 100-W is equipped with a stainless steel Inox-Radial heat exchanger. Developed and manufactured by Viessmann, this high-quality stainless steel component maximizes performance and reliability. Plus, the self-cleaning heat exchanger† contributes to the boiler's long service life and dependable performance.

BENEFITS AT A GLANCE

- + Long lasting, reliable performance and outstanding 95% AFUE efficiency with stainless steel Inox-Radial heat exchanger
- + Reduced emission (low-NOx) and 10:1 turn down ratio with fully-modulating stainless steel MatriX Plus cylinder burner
- + Field height adjustable controls for comfortable service operation in any space
- + Compact, lightweight wall-mount design with zero clearance to combustibles
- + Easy installation, service and maintenance with easy access to all servicable components
- + Multiple venting options and advanced software allow for automatic adjustment
- + Easy piping due to two sets of tapings, along with built in pump and diverter
- + Suitable for high altitudes up to 10,000 ft (3000 m) with no power loss and automatic software vent length adjustment
- + Built-in automatic frost protection
- + Reliable on demand domestic hot water (B1KE)
- + Limited lifetime warranty for added peace of mind

Warranty information is available at viessmann-us.com/warranty

† Self-cleaning heat exchanger does not eliminate need for regular servicing.

User-Friendly Control Unit


The Vitodens 100-W range of condensing boilers utilizes a simple and easy-to-navigate user interface. The black control panel display offers discrete design and height adjustment of a single zone circuit or multiple zones with standard field installed zone control panel. The control panel features intuitive homeowner dashboards for basic settings and operational insights, as well as advanced dashboards for service and trouble shooting, available in multiple languages.

Helps You Save

Select an easy-to-use room thermostat and utilize the boiler's on-board control, which automatically adjusts the boiler water to outdoor temperatures. This not only boosts fuel savings, but also keeps your home warm and comfortable at all times.

STANDARD EQUIPMENT INCLUDES

- + Wall-mounted condensing boiler
- + Wall bracket mounting kit
- + Safety valve 30 psi and 150 psi (B1KE models)
- + DHW sensor (B1HE models)
- + Pressure gauge
- + Two fill/drain valves
- + Air supply cover
- + Outdoor temperature sensor
- + LPG conversion labeling kit
- + Flexible discharge tubing (condensate)



Actual product may vary from illustrated image

VITODENS 100-W

Model B1KE-120


- 1 Inox-Radial stainless steel heat exchanger
- 2 Stainless steel MatriX Plus burner and Lambda Pro Plus combustion control
- 3 Burner blower
- 4 Gas and hydronic connections
- 5 Field adjustable lightguide and 3.5" LCD controls display
- 6 Integrated high efficiency boiler and DHW pump
- 7 DHW plate heat exchanger (combi models only)

Wall-Hanging Condensing Boiler

VITODENS 100-W

Model 85/120 shown

Front view



Side view

VIESSMANN

Viessmann Manufacturing

Company Inc.

Warwick, RI, 02886

1-800-288-0667

viessmann-us.com

Legend

- (A) Safety valve, pressure gauge connection
- (B) Condensate drain
- (C) Heating system supply
- (D) For B1HE series, DHW tank heating supply
For B1KE series, DHW supply
- (E) For B1HE series, DHW tank heating return
For B1KE series, DCW inlet
- (F) Heating system return
- (G) Fuel gas connection

Vitodens 100-W B1HE, B1KE

		B1HE-85	B1HE-120	B1HE-150	B1HE-199	B1KE-120	B1KE-199
CSA Input (NG and LPG)	MBH	85	120	150	199	120	199
	kW	24.9	35.2	44	58.3	35.2	58.3
CSA Output (NG and LPG)¹	MBH	80	113	141	187	113	187
	kW	23.4	33.1	41.3	54.8	33.1	54.8
Net AHRI Rating²	MBH	70	98	123	163	98	163
	kW	20.5	28.7	36	47.8	28.7	47.8
A.F.U.E.	%	95	95	95	95	95	95
Overall Dimensions							
Depth	inches	19.75	19.75	21.75	21.75	19.75	21.75
	mm	500	500	550	550	500	550
Width	inches	17.75	17.75	17.75	17.75	17.75	17.75
	mm	450	450	450	450	450	450
Height	inches	33.75	33.75	39	39	33.75	39
	mm	859	859	989	989	859	989
Weight	lbs	108	108	179	179	110	190
	kg	49	49	81	81	50	86
Boiler Water Content	USG	1.02	1.02	2.5	2.5	1.02	2.5
	L	3.88	3.88	9.5	9.5	3.88	9.5
Max. Flow Rate⁴	GPM	4.8	6.2	8.8	10.6	6.2	10.6
	L/H	1090	1408	1999	2408	1408	2408
Heat Exchanger Surface Area	ft ²	12.96	12.96	27.44	27.44	12.96	27.44
	m ²	1.2	1.2	2.55	2.55	1.2	2.55
Maximum Operating Pressure (max. allowable working pressure) at 210°F (99°C)	psig	45	45	60	60	45	60
	bar	3	3	4	4	3	4
Minimum/Maximum Gas Supply Pressure³							
Natural Gas	"w.c.			4 / 14			
LPG	"w.c.			10 / 14			
Boiler Water Temperature							
Space Heating (steady state)	°F (°C)			68-180 (20-82)			
DHW Tank Heating	°F (°C)			194 (90)			
DHW Heating	°F (°C)			194 (90)			
Fixed High Limit (FHL)	°F (°C)			210 (99)			
Boiler Connections							
Gas Supply Connection	NPTF (female)			3/4 inch			
Pressure Relief Valve	NPTF (female)			3/4 inch			
Boiler Heating Supply and Return	NPTM (male)	3/4 inch	3/4 inch	1 inch	1 inch	3/4 inch	1 inch
DHW Tank Heating Supply/Return	NPT	3/4 inch	3/4 inch	1 inch	1 inch	-	-
DHW Heating (combi)	NPTM (male)	-	-	-	-	3/4 inch	1 inch
Drain Valve	(male thread)			3/4 inch			
Boiler Flue Gas Connection	Ø in			3			
	Ø mm			80			

1 Output based on 140°F (60°C), 120°F (49°C) system supply / return temperature.

2 Net AHRI rating based on piping and pick-up allowance of 1.15.

3 If the gas supply pressure exceeds the maximum gas supply pressure value, a separate gas pressure regulator must be installed upstream of the heating system.

4 See "System Flow Rates" on page 11 of product Technical Data Manual



Technical information subject to change without notice.

9450380 06/2021 Printed in USA