MODEL NUMBER	VOLTAGE	DESCRIPTION	APPLI- CATION*	PART NO.
-----------------	---------	-------------	-------------------	----------

PUMP CONTROLLER / LOW WATER CUT-OFF COMBINATIONS

250	120VAC	Controls boiler feed pump to maintain boiler water level. Provides low water cut-off protection. Includes manifold	4	45-250
250WC		casting with three model EL1214 probes. WC model includes water column manifold model 1214C-1.	4	45-252



FLOW SWITCHES

FS200	N/A	Replaces Model 44-100. General purpose liquid flow switch, 160 PSI, fits 1" to 6" pipe. General purpose enclosure.	Multi- Purpose	44-200
FS204	N/A	General purpose liquid flow switch, 160 PSI, fits 1" to 6" pipe. NEMA 4 enclosure.	Multi- Purpose	44-204



WATER METER

WM-1	 General purpose, heavy-duty water meter with 3/4" adaptors	Multi-	45-130
	rated from ,5gpm to 35gpm,	Purpose	



HI WATER LIMIT & TANK LEVEL / PUMP CONTROLLERS

270SV	120VAC	High water limit control. Interrupts power to pump/feeder in high water condition. Provides alarm contacts. Includes EL1214-SV probe suitable for mounting in standard black tee.	Multi- Purpose	45-270
727	120VAC	Maintains high level. Contacts make to start pump on low level. Includes one EL1214-SV, and one EL1214-RSV probe.	Multi- Purpose	45-727
787	120VAC	Maintains low level. Contacts make to start pump on high level. Includes one EL1214-SV, and one EL1214-RSV probe.	Multi- Purpose	45-787



ACU-TEMP TEMPERATURE CONTROL

2000 24VA	C Controls water temperature in indirect water heaters. Closely monitors the rate of temperature changes and controls the heating source to minimize fluctuations in tank temperature, while optimizing fuel efficiency. Includes two 90" sensors (1 with 3/8" head; 1 with 1/4" head).	Multi- Purpose	46-2000
------------------	---	-------------------	---------



2000