



Toilet tank with ContinuousClean, 1.28 gpf K-5711

Features

- ContinuousClean system automatically dispenses cleaning solution with every flush.
- Works with any white toilet bowl cleaner tablet. Tablets last for more than one year in ContinuousClean system.
- 1.28 gpf (4.8 lpf).
- Standard left-hand Polished Chrome trip lever included.
- Combines with the K-4144 bowl to create a complete K-5709 Corbelle ContinuousClean toilet.

Technology

- Adjustment dial lets you set how much cleaning solution is dispensed with every flush.
- Optional: uses two AAA batteries (included) to power the LED system indicator light. System indicator light will notify user when system is working properly and when to replace cleaning agent or batteries.
- Single-flush gravity uses the force of gravity and a precision-engineered tank, bowl, and trapway to create a strong siphon during flushing.
- AquaPiston® canister allows water to flow out of the tank from all sides (360 degrees), increasing the power and effectiveness of the flush.
- Flush valve's 3:2 ratio harnesses the natural force of gravity and optimizes flush performance.
- Durable canister design has 90% less exposed seal material than a 3" flapper for leak-free performance.

Installation

Supply line sold separately.

Recommended Products/Accessories

K-20120-L Trip Lever K-4144 Elongated chair height toilet bowl K-23726 Drain treatment

Included Components

Additional Components:

Tank Cover, Trip Lever, and Hardware kit



Codes/Standards

ASME A112.19.2/CSA B45.1

KOHLER® Toilets and Seats Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Joior	Code	Description
	0	White
	96	Biscuit
7.75	NY	Dune
500	95	Ice™ Grey
100	G9	Sandbar
4157	7	Black Black™





Corbelle®

Toilet tank with ContinuousClean, 1.28 gpf K-5711

No image available. This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal.

Water Consumption
Full: 1.28 gpf (4.8 lpf)

Notes

Install this product according to the installation instructions.

