

K	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com							LOCATION																																																
	ADJUSTABLE FIXTURE SUPPORTS FOR SIPHON JET WATER CLOSETS - SHALLOW ROUGH-IN TYPE																																																							
	NO-HUB VERTICAL FITTINGS																																																							
	SINGLE Rear Support Lug and -M51 Anchor Foot Assembly Regularly Furnished.					DOUBLE																																																		
DRAWING NUMBER	S0230Y		SIZE	A		SCALE:	NONE		DATE:	2-28-86																																														
WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA																																																								
Fig. 0230Y Side View																																																								
Fig. 0230DY Side View																																																								
Front View																																																								
NOTE: Base support must be securely anchored to floor (with four 1/2" (13) bolts provided by contractor). NOTE: Dimensions shown in parentheses are in millimeters. NOTE: 1 1/2" or 2" tapped inlet available.																																																								
The water closet gasket regularly furnished is made of molded neoprene and designed to fit water closet outlet dimensions and configurations shown in ANSI Standard A112.19.2M-1995, Figure 13B. If gasket is not found to be compatible to fixture due to nonconformance of said fixture to ANSI A112.19.2M, then fixture manufacturer shall be consulted for a suitable gasket recommendation. Jay R. Smith assumes no liability for connections to fixtures which do not conform to these standards.																																																								
*NOTE: 9" (230) core drilled hole is required for rough-in 4 1/4 (110) thru 6 1/2 (165).																																																								
<table border="0" style="width: 100%;"> <tr> <td style="width: 20px;">□</td> <td>Fig. 0230Y . . . NO-HUB</td> </tr> <tr> <td style="width: 20px;">□</td> <td>Fig. 0230DY . . . NO-HUB Double</td> </tr> </table>												□	Fig. 0230Y . . . NO-HUB	□	Fig. 0230DY . . . NO-HUB Double																																									
□	Fig. 0230Y . . . NO-HUB																																																							
□	Fig. 0230DY . . . NO-HUB Double																																																							
<table border="1" style="width: 100%; border-collapse: collapse; font-size: small;"> <tr> <th rowspan="2">A SIZE</th> <th rowspan="2">C</th> <th colspan="2">D</th> <th rowspan="2">E</th> <th rowspan="2">F</th> </tr> <tr> <th>MIN</th> <th>MAX</th> </tr> <tr> <td>4 (100)</td> <td>9 (230)</td> <td>1 1/2 (38)</td> <td>4 1/4 (110)</td> <td>14 (355)</td> <td>2 1/4 (57)</td> </tr> <tr> <td>5 (125)</td> <td>11 1/2 (290)</td> <td>1 1/2 (38)</td> <td>4 1/4 (110)</td> <td>11 1/2 (290)</td> <td>2 3/4 (70)</td> </tr> <tr> <td>6 (150)</td> <td>11 1/2 (290)</td> <td>1 1/2 (38)</td> <td>4 1/4 (110)</td> <td>11 1/2 (290)</td> <td>3 1/4 (83)</td> </tr> </table>												A SIZE	C	D		E	F	MIN	MAX	4 (100)	9 (230)	1 1/2 (38)	4 1/4 (110)	14 (355)	2 1/4 (57)	5 (125)	11 1/2 (290)	1 1/2 (38)	4 1/4 (110)	11 1/2 (290)	2 3/4 (70)	6 (150)	11 1/2 (290)	1 1/2 (38)	4 1/4 (110)	11 1/2 (290)	3 1/4 (83)																			
A SIZE	C	D		E	F																																																			
		MIN	MAX																																																					
4 (100)	9 (230)	1 1/2 (38)	4 1/4 (110)	14 (355)	2 1/4 (57)																																																			
5 (125)	11 1/2 (290)	1 1/2 (38)	4 1/4 (110)	11 1/2 (290)	2 3/4 (70)																																																			
6 (150)	11 1/2 (290)	1 1/2 (38)	4 1/4 (110)	11 1/2 (290)	3 1/4 (83)																																																			
© dimension = 4" (100) (regularly furnished) consisting of nipple and Adjus-to-Wall coupling permitting adjustment from 3" (76) min. to 4" (100) max.																																																								
<table border="1" style="width: 100%; border-collapse: collapse; font-size: small;"> <tr> <td style="width: 30px;">K</td> <td style="width: 100px;">5-3-02</td> <td style="width: 200px;">Added Note 1 1/2 or 2 tapped</td> <td style="width: 30px;">RN</td> <td style="width: 30px;">BS</td> <td style="width: 100px;">WEIGHT</td> <td style="width: 100px;">VOLUME</td> <td style="width: 150px;">FIGURE NUMBER</td> </tr> <tr> <td>J</td> <td>10/09/99</td> <td>Deleted Note</td> <td>JJ</td> <td>BS</td> <td>POUNDS</td> <td>CUBIC FEET</td> <td rowspan="4" style="text-align: center; font-size: 2em; font-weight: bold;">0230Y</td> </tr> <tr> <td>H</td> <td>7-1-98</td> <td>Submittal Update</td> <td>ASL</td> <td>BS</td> <td></td> <td></td> </tr> <tr> <td>G</td> <td>1-23-98</td> <td>Chg'd Callout</td> <td>EMB</td> <td>BS</td> <td></td> <td></td> </tr> <tr> <td>F</td> <td>6-1-95</td> <td>Added Millimeters</td> <td>EMB</td> <td>BS</td> <td></td> <td></td> </tr> <tr> <td>REV.</td> <td>DATE</td> <td>DESCRIPTION</td> <td>BY</td> <td>CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>												K	5-3-02	Added Note 1 1/2 or 2 tapped	RN	BS	WEIGHT	VOLUME	FIGURE NUMBER	J	10/09/99	Deleted Note	JJ	BS	POUNDS	CUBIC FEET	0230Y	H	7-1-98	Submittal Update	ASL	BS			G	1-23-98	Chg'd Callout	EMB	BS			F	6-1-95	Added Millimeters	EMB	BS			REV.	DATE	DESCRIPTION	BY	CKD. BY			
K	5-3-02	Added Note 1 1/2 or 2 tapped	RN	BS	WEIGHT	VOLUME	FIGURE NUMBER																																																	
J	10/09/99	Deleted Note	JJ	BS	POUNDS	CUBIC FEET	0230Y																																																	
H	7-1-98	Submittal Update	ASL	BS																																																				
G	1-23-98	Chg'd Callout	EMB	BS																																																				
F	6-1-95	Added Millimeters	EMB	BS																																																				
REV.	DATE	DESCRIPTION	BY	CKD. BY																																																				



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

C	DRAWING NUMBER S0200BS	SIZE A	SCALE: NONE	DATE: 2-28-86	APPROVED BY: JD	CHECKED BY: CR	DRAWN BY: VGD	0200/0300 Series Back Sheet	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com	ASPE	PD	LOCATION
									MODIFICATIONS & VARIATIONS			
									Ⓒ DIMENSION - ADJUS-TO-WALL TYPE OUTLET CONNECTION The Smith Adjus-to-Wall outlet connection provides adjustment at the face of the wall at the time the fixture is set; thus, compensating for wall construction variations. The Ⓒ dimension is measured from the front of the face plate to the finished wall. To properly determine the length of nipple required, deduct 1" (25) from the Ⓒ dimension. When the Ⓒ dimension exceeds 7" (180), the -M40 Wide Pipe Chase Support is recommended. The Adjus-to-Wall coupling will provide 1/2" (13) horizontal adjustment in either direction with the coupling extended 5/16" (8) past face of the finished wall. Ⓒ dimension = 4" (100) (regularly furnished) consisting of nipple and adjus-to-wall coupling permitting adjustment from 3" (76) min. to 4" (100) max. *ABS (Regularly Furnished) other length PVC.			
									RECOMMENDED SETTING OF CLOSET OUTLET CONNECTION AND FIXTURE STUDS Manufacturers have slight differences in the depth of the closet horn and flange thickness of their closets. Usually the fixture support closet connection should extend 5/16" (8) beyond face of finished wall (Dimension "R") and the fixture studs 2 1/4" (57) (Dimension "X"). For exact dimensions please use the formulas below. DETAIL A Formula for "R" is: $S + 1/16" (2) - D = R$ S = Depth of closet horn 1/16" (2) = Distance closet is to set away from finished wall. D = 1/2" (13) for felt gasket and 3/8" (10) for neoprene gasket. R = Distance coupling should extend beyond finished wall. NOTE: When the fixture is installed, closet gasket must be compressed sufficiently to assure a gas and water-tight seal. DETAIL B Formula for "X" is: $Y + 1/16" (2) + 9/16" (14) = X$ Y = Thickness of closet wall flange. 1/16" (2) = Distance closet is to set away from finished wall. X = Distance supporting stud should extend beyond finished wall. NOTE: Bearing nuts and washers must be set to take full loading from the fixture allowing 1/16" (2) clearance between fixture and wall.			
									CONCEALED FLUSH VALVES A concealed flush valve when used with a blowout water closet support will not clear the face plate. Therefore 4 1/2" (115) to 6 1/2" (165) is required from back of wall to face plate to permit the installation of the concealed flush valve piping.			
FIGURE NUMBER	C B A	12-10-03 6-1-95 7-1-93	Revised Notes Added Millimeters Submittal Update	RN EMB EMB	CL BS BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 0200/0300 Series Back Sheet				
REV.	DATE	DESCRIPTION			BY	CKD. BY						



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov