

**Product**
**AutoSnap® Coupling Assembly for TracPipe and CounterStrike**
**Project Information**

Job Name:	Date Submitted:
Location:	Submitted By:
Engineer:	Approved By:
Contractor:	Manufacturer's Rep:

**Installation**

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

**Application Information**

Coupling fitting for use between like sizes of TracPipe or CounterStrike Tubing.  
 For indoor, outdoor, and concealed location applications.

**Technical Data**
**Materials**

Nut, Adapter, and Snap Ring      Yellow Brass

**Pressure Ratings (used with tubing)**

Specification Operating Pressure      25 PSIG  
 CSA International Evaluation Report - Max Operating Pressure,  
 3/8" through 1-1/4"      125 PSIG

**Temperature Ratings (used with tubing)**

Operating Temperature Range      -20 to 200 Deg F


**Codes**

ICC Codes (IFGC, IRC, IMC, IPC), NFPA 54, UPC, CAN/CSA B149.1, NFPA 58

**Standards**

ANSI LC1 / CSA 6.26, ANSI Z223.1

**Listings**

CSA

**Dimensional Information**

✓	Size	P/N	Diameter across flats (Nom. in.)	Fitting length (Nom. in.)	TracPipe or CounterStrike Size	Weight (lbs)
<input type="checkbox"/>	3/8"	FGP-SCPLG-375	15/16"	2-3/8"	3/8" X 3/8"	0.3
<input type="checkbox"/>	1/2"	FGP-SCPLG-500	1-1/8"	2-3/4"	1/2" X 1/2"	0.5
<input type="checkbox"/>	3/4"	FGP-SCPLG-750	1-3/8"	2-7/8"	3/4" X 3/4"	0.7
<input type="checkbox"/>	1"	<b>FGP-SCPLG-1000</b>	1-3/4"	3-1/8"	1" X 1"	0.9
<input type="checkbox"/>	1-1/4"	FGP-SCPLG-1250	2"	3-1/2"	1-1/4" X 1-1/4"	2.0
<input type="checkbox"/>	1-1/2"	FGP-SCPLG-1500	2-3/8"	4"	1-1/2" X 1-1/2"	3.3
<input type="checkbox"/>	2"	FGP-SCPLG-2000	2-7/8"	4-5/8"	2" X 2"	5.5

Omega Flex, Inc. \* 451 Creamery Way\* Exton, PA 19341

Tel: 610-524-7272 \* Toll Free: 800-671-8622 \* Fax: 610-524-7282

www.omegaflex.com

FGP-SUB-039

Rev. 03-15

TracPipe, CounterStrike, PS-II, AutoFlare, and AutoTrip are registered trademarks of Omega Flex, Inc.

page 1/1