





Product AutoSnap® Straight Fitting (Male-NPT) Assembly for TracPipe and CounterStrike Project Information Job Name: Date Submitted: Location: Submitted By: Engineer: Approved By: Contractor: Manufacturer's Rep: Installation Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

Application Information

Transition fitting between TracPipe or CounterStrike Tubing and NPT thread. Fitting thread is Male NPT. For use indoor, outdoor, and concealed location applications.

Technical Data

Materials

Nut, Adapter, and Snap Ring Yellow Brass

Pressure Ratings (used with tubing)

Specification Operating Pressure 25 PSIG
CSA International Evaluation Report - Max Operating Pressure,
3/8" through 1-1/4" 125 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range -20 to 200 Deg F

Codes

ICC Codes (IFGC, IRC, IMC, IPC), NFPA 54, UPC, CAN/CSA B149.1, NFPA 58

Standards

ANSI LC1 / CSA 6.26. ANSI Z223.1

Listings

CSA, ICC PMG 1046 / 1058,

Dimensional Information Diameter Fitting TracPipe or CounterStrike Male NPT across flats length P/N (Nom. in.) (Nom. in.) Pipe size Weight (lbs) Size Size 3/8" FGP-SFST-375N 15/16" 3/8" 2-1/8" 3/8" 0.2 3/8"x1/2" FGP-SFST-375 15/16" 2-1/8" 3/8" 1/2" 0.2 1/2" FGP-SFST-500 1-1/8" 2-1/8" 1/2" 1/2" 0.3 1/2"x3/4" 2" 1/2" 3/4" FGP-SRST500-750 1-1/8" 0.4 3/4" 3/4" FGP-SFST-750 1-3/8" 2-1/4" 3/4" 0.4 3/4"x1/2" FGP-SRST750-500 1-3/8" 2" 3/4" 1/2" 0.5 1" 1" FGP-SFST-1000 1" 1-3/4" 2-1/2" 0.7 1"x3/4" 1" 3/4" FGP-SRST1000-750 1-3/4" 2-1/8" 0.8 2" 1-1/4" 1-1/4" 1-1/4" FGP-SFST-1250 2-3/4" 0.9 1-1/2" FGP-SFST-1500 2-3/8" 3-1/4" 1-1/2" 1-1/2" 1.3 2" FGP-SFST-2000 2-7/8" 3-1/2" 2" 2" 2.15