



# SANIFLUSH TWO-PIECE ROUND TOILET SYSTEM

**Close-Couple Toilet – 1.28 GPF (4.8 Liter Flush)**

## **SANIFLUSH 083 & 005**

### ✓ **083 Round Bowl**

- Vitreous china
- Integral P-trap and a rear outlet spigot
- Seating height: 16 ¾" (without seat)
- Large 3" trapway
- Wash down style toilet
- Low flush toilet; it uses 1.28 gallons (4.8 L) per flush
- Toilet supplied with a set of lag screws, plastic anchors and china protectors
- Water spot measures 4 ½" x 3 ¾"
- 1 Year limited warranty

### ✓ **005 Toilet Tank**

- Vitreous china
- Insulated tank to prevent condensation
- The zero re-fill fill valve is easily adjustable
- The flush valve has a silicone flapper seal
- Tank is not designed to be used with refill hose thus not provided.
- Water level mark applied to the overflow tube
- Toilet tank supplied with bowl screws, washers and wing nuts
- 1 year limited warranty
- Warranty for fill and flush valve as per manufacturer

### **Nominal Dimensions**

31" x 17-3/4" x 27"  
(787mm x 451mm x 686mm)

### **Fixture Dimensions and Hydraulic Performance - Meets or Exceeds the Following Specifications**

- ANSI/ASME A112.19.2M and CAN/CSA B45 Requirements
- IAPMO/UPC Certificate of Listing
- EPA WaterSense labeled

### **Notes**

- Available in white only
- Includes soft-close toilet seat along with mounting hardware kit Part# SEATROUND
- Replacement fill valve recommended – Fluidmaster 400A or equal (not supplied)



*Round Bowl with Tank (083 & 005)*

### **Care & Cleaning**

- When cleaning toilet, wash it with mild soapy water or liquid cleaners that are not chlorine or bleach based. Avoid using harsh detergents.
- We do not recommend the use of in-tank cleansers. Products containing chlorine can cause damage to components inside the tank and cause them to fail prematurely.





# SANIFLUSH TWO-PIECE ROUND TOILET SYSTEM

Close-Couple Toilet – 1.28 GPF (4.8 Liter Flush)

**SANIFLUSH 083 & 005**

## Drawings and Dimensions

