

## SPECIFICATIONS

Water Use:	1.0 GPF & 0.8 GPF (3.8 LPF & 3.0 LPF)
Flush System:	TORNADO FLUSH
Water Pressure:	Flowing: Min 7.25 PSI (0.05MPa) Static: Max 108.75 PSI (0.75 MPa)
Water Surface:	8-1/2" x 7-1/2"
Trap Diameter:	2" (51 mm)
Trap Seal:	2-1/8" (55 mm)
Warranty:	Three Year Limited (Residential) One Year Limited (Commercial)
Material:	Bowl: Vitreous china Seat + Cover: Plastic
Power Rating:	AC 120 V, 60 Hz, 1300 W
Power Cord:	1.2 m (3.94 ft)
Water Feature:	Adjustable Water Flow Rate
Rear Washing:	Approx. 0.08 - 0.11 gal/min
Soft Washing:	Approx. 0.08 - 0.11 gal/min
Front Washing:	Approx. 0.08 - 0.11 gal/min
Wide Front Washing:	Approx. 0.09 - 0.11 gal/min
Washing Spray Temperature:	Approx: 86°F - 104°F (30°C - 40°C)
Safety Feature:	Temperature Fuse
Drying Feature:	Air Temperature: Approx: 95°F - 140°F (35°C - 60°C)
Airflow Volume:	10.24 ft <sup>3</sup> /min
Safety Feature:	Temperature Fuse
Seat Warming Feature:	Surface Temperature: Approx: 82°F - 97°F (28°C - 36°C)
Seat Heater Capacity:	542 W
Safety Feature:	Temperature Fuse
Air Purifying Feature:	O <sub>2</sub> Deodorizer
Air Volume:	5.65 ft <sup>3</sup> /min
Ambient Temperature Range:	32°F/0°C to 104°F/40°C
Product Size:	31-1/2" L x 18-7/16" W x 23" H
Weight:	Approximately 141 lbs.
Floor to Seat Height:	17 5/16" (440mm)
Shipping Weight:	156.5 lbs. (71kg)
Shipping Dimensions:	36-3/4" (933mm) L x 21" (545mm) W x 31" (802mm) H

## INSTALLATION NOTES

- For use with potable water only. Do not use with recycled water.

