C.C. RUST-X RUST INHIBITOR AND BOILER TREATMENT

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure, or Accident - Call INFOTRAC - Day or Night: 1-800-535-5053

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

PRODUCT IDENTIFICATION

DOT Shipping name: CLEANING COMPOUNDS, NOI CAS NO.: MIXTURE Chemical Family: Phosphates UN/NA#: NR

DOT Hazard Class: NR DATE OF ISSUE: 2018/06/22

SECTION I - HAZARDOUS INGREDIENTS/EXPOSURE LIMITS

Hazardous Ingredients: CAS # TLV/PEL AGENCY TYPE SARA-313(% Range)

NONE

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

WARNING: CORROSIVE

EYE CONTACT: Move person away from exposure and into fresh air. If irritation or redness develops, flush eyes with clean water and seek medical attention. For direct contact hold eyelids apart for at least 15 minutes. **Seek medical attention**.

SKIN CONTACT: Remove contaminated shoes and clothing and cleanse affected areas thoroughly by washing with mild soap and water.

If irritation persists seek medical attention.

INHALATION: (breathing) Not expected to be a hazard under normal operating conditions...

INGESTION: (swallowing) If swallowed, seek emergency medical attention. Do not give anything by mouth. .

SECTION III - HEALTH HAZARDS / ROUTES OF ENTRY

EYE CONTACT: One or more components of this material may be an eye irritant.

SKIN CONTACT: Continuous contact with this material may cause drying of skin. Chemical itself is an irritant or sensitizer.

SKIN ABSORPTION: Symptoms of toxicity are anticipated by this route .

INHALATION: (breathing) Not expected to be a hazard under normal operating conditions.

INGESTION: (swallowing) Ingestion of large quantities may cause the following: Irritation of digestive tract, signs of nervous system depression, such as headache, drowsiness, dizziness, loss of coordination, fatigue, and nausea.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION Adequate ventilation is recommended when working with chemical products.

RESPIRATORY PROTECTION: The use of respiratory protection is recommended.

PROTECTIVE GLOVES: The use of gloves impermeable to the specific material handled is advised to prevent possible irritation. **EYE PROTECTION**: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.

SECTION V - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: (materials to avoid) This product is incompatible with: Oxidizing agents, strong acids and bases

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition in the presence of air may yield carbon monoxide, carbon

dioxide.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF LEAK OR SPILL Stop spill/release if it can be done without risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Prevent spilled material from entering sewers, storm drains, and natural waterways. Dike far ahead of spill for later recovery and disposal. Spilled material may be absorbed by an appropriate absorbent.

WASTE DISPOSAL METHOD: Dispose of product in accordance with local, county, state, and federal regulations.

Page 1 18-205

C.C. RUST-X RUST INHIBITOR AND BOILER TREATMENT

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: Do not get in eyes, skin or clothing. Do not breathe vapor mist or gas. Use good personal hygiene practices. Containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: Extinguish with dry chemical, CO₂, or a universal type foam.

FIRE AND EXPLOSION HAZARD: May decompose during contact with flames, heating elements, or in combustion engines releasing irritating gases. Container may explode if heated due to resulting pressure rise.

FIRE FIGHTING PROCEDURES: Wear appropriate protective equipment including respiratory protection as conditions warrant (**see Section IV**). Stop spill/release if it can be done without risk. Water spray may be useful in minimizing or dispersing vapors and cooling equipment exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes.

SECTION IX - PHYSICAL DATA

APPROXIMATE BOILING POINT (DEG F): >200

SPECIFIC GRAVITY (68 F): >1

RELATIVE EVAPORATION RATE (ESTIMATED):<1
VAPOR PRESSURE @20C mmHg (CALCULATED):<1

PER CENT VOLATILE: NONE FLASH POINT (TCC, DEG F): NONE PER CENT SOLUBILITY IN WATER: 100

SECTION X - OTHER REGULATORY DATA

<u>SARA</u> <u>HMIS</u>

SECTION 302: NONEHealth:1SECTION 311 & 312: NONEFlammability:0SECTION 313: See Section I.I NONEReactivity:0

TSCA

with the TSCA inventory. NOT LISTED CERCLA

RCRA

NOT REGULATED SODIUM TRIPOLY PHOSOPHATE RQ: 5000 LBS.

CARCINOGENICITY:

NOT LISTED with NTP or IARC.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufactures and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

18-205

Page 2 18-205