

quality . service
innovation . integrity

2000 High Temperature Intermittent



Features

This series of submersible pumps is designed for use in residential or commercial dewatering applications and can be used to transfer groundwater and wastewater. These durable cast iron pumps include a powder coated epoxy finish to prevent corrosion, and are designed to meet specifications with assurance by using high temperature parts rated for intermittent 200° F (93° C) contact, ensuring a long service life. As with every Zoeller® pump, each one is 100% factory tested to ensure quality and reliability for years of trouble-free performance! This attention to detail is an inherent feature of every model in this pump series, making it one of the most reliable in the industry.

Specifications

Motor Characteristics

Motor	3/10 - 1/2 HP
Voltage	115 or 230 V
Phase	1 Ph
Hertz	60 Hz
RPM	1725 RPM
Amps	4.7 - 10.7 Amps

Pump Characteristics

Operation	Nonautomatic
Discharge Size	1-1/2" - 3"
Cord Length	15' (5 m) standard
Cord Type	High-temperature, 16-gauge heavy-duty SOOW cord
Max Head	25' (7.6 m)
Max Flow Rate	115 GPM (435 LPM)
Max Operating Temp	200° F (93° C)
Cooling	Oil filled
Motor Protection	High temperature thermal overload

Materials Characteristics

Motor Housing	Cast iron
Pump Housing	Cast iron
Base	Cast iron
Upper Bearing	Varies based on package
Lower Bearing	Varies based on package
Mechanical Seals	Carbon and NI-resist
Impeller Type	Non-clogging vortex
Impeller	Cast iron
Hardware	Stainless steel
Motor Shaft	AISI cold rolled steel
Gasket	Neoprene

60 Hz





PUMP COMPANY

Zoeller Family of Water Solutions™

FM1922_Ea

2000 High Temperature Intermittent



Model

Model Number	Seal	Mode	Volts	Phase	Amps	HP	Hz	Lbs	Kg
BN2057	Single	Non	115	1	9.7	3/10	60	28	13
BE2057	Single	Non	230	1	4.8	3/10	60	28	13
BN2098	Single	Non	115	1	9.4	1/2	60	39	18
BE2098	Single	Non	230	1	4.7	1/2	60	39	18
BN2137	Single	Non	115	1	10.7	1/2	60	46	21
BE2137	Single	Non	230	1	5.8	1/2	60	46	21
BN2282	Single	Non	115	1	10.3	1/2	60	84	38
BE2282	Single	Non	230	1	5.0	1/2	60	84	38

Your Peace of Mind is Our Top Priority®
3649 Cane Run Rd | Louisville, KY 40211 USA

+1 502-778-2731 | 1-800-928-7867 | Fax: +1 502-774-3624
www.zoeller.com

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies. Copyright Zoeller Company. All rights reserved.